

TRIPLE POWER

- Safest LiFePO₄ battery
- 90% DOD
- Cycle life > 6000 times
- IP55 protection level
- Floor or wall mounting
- Less self consumption
- Quick installation
- No toxic heavy metals or caustic materials



TRIPLE
POWER

Global: +86 571-56260011

Email: info@triple-power.com

T-BAT SYS-HV Configuration List

T-BAT H 5.8

Nominal Voltage [V]	115.2
Operating Voltage [V]	100-131
Battery Type	Li-on (LFP)
Nominal Capacity [kWh]	5.8
Usable Capacity [kWh]	5.2
Faradic Charge Efficiency [%]	99
Battery Roundtrip Efficiency [%]	95
Standard Power [kW]	2.9
Max Power [kW]	4.0
Recommend Charge/Discharge Current [A]	25
Max Charge/Discharge Current [A]	35
Cycle Life [90% DOD]	>6000 Cycles
Warranty [Year]	10
Available Operating Temperature Range [°C]	0 to 55
Full-load Operating Temperature Range [°C]	5 to 48
Humidity [%]	4 to 100 (condensing)
Altitude [m]	Below 2000
Protection	IP55
System to Inverter	CAN2.0
Battery to Battery/BMS	RS485
Data Collection Port /FW UPDATE	CAN2.0
Master Control Working Mode Indicator	1 LED
Master Control Capacity Indicator	4LED (25%, 50%, 75%, 100%)
Battery Module LED	2 LED
Reset	Button
Switch ON/OFF	Button*1 + breaker*1
Safety	CE, RCM, TUV(IEC62619) UL1973,ROHS,REACH
UN Number	UN3840
Hazardous Materials Classification	Class 9
Transport Testing Requirement	UN38.3
Dimensions(LxWxH) [mm]	474*193*708 (T-BAT H 5.8) / 474*193*647 (HV11550)
Weight [kg]	72.2 (T-BAT H 5.8) / 68.5 (HV11550)

*The Triple Power battery could be scalable up to 4 modules, for a total of 23.2kWh.



X1-AC

3.0kW/3.6kW/4.6kW/5.0kW

Features:

- Natural Cooling, quiet and low maintenance
- Max Efficiency up to 97%
- Multiple protection: RCD, isolation, over voltage
over temperature, earth protection, short-circuit protection, etc
- Compatible with High-voltage batteries
- Transformerless design with software and hardware protection.



Get in touch now:

Global: +86 571-56260008
AU: +61 1300 476529

DE: +49 7231 4180999
UK: +44 2476 586998

Website: www.solaxpower.com
Email: info@solaxpower.com



X1-AC-3.0

X1-AC-3.6

X1-AC-4.6

X1-AC-5.0

OUTPUT AC				
Nominal AC power [VA]	3000	3680	4600	4999
Max. apparent AC power [VA]	3000	3680	4600	4999
Rated grid voltage (range) [V]	220/230/240 (180 to 280)			230/240 (180 to 280)
Rated grid Frequency[Hz]	50/60			
Nominal AC current[A]	13	16	20	21.7
Max. AC current[A]	13.6	16.8 (16 for G83)	21	21.7
Max. overcurrent protection[A]	45			
Displacement power factor	0.8 leading to 0.8 lagging			
THDi, rated power [%]	<2			
Load control	Optional			
INPUT AC				
Nominal AC power[VA]	3000	3680	4600	4999
Max. apparent AC power[VA]	3000	3680	4600	4999
Rated grid voltage(range)[V]	220/230/240 (180 to 280)			
Rated grid frequency[Hz]	50/60			
Nominal AC current[A]	13	16	20	21.7
Max.AC current[A]	13.6	16.8 (16 for G83)	21	21.7
Max. short current(Isc)[A]	45			
Displacement power factor	0.8 leading to 0.8 lagging			
BATTERY				
Battery type	Lithium/Lead-acid battery			
Battery voltage range[V]	70-400			
Recommended battery voltage[V]	300			
Rated charge/discharge current[A]	25			
Max. charge/discharge current[A]	35	35	30	30
Communication interfaces	CAN			
Reverse connect protection	Yes			
EFFICIENCY				
Max. efficiency	97.00			
Max. Battery charge efficiency (AC to BAT)(@full load) [%]	97.00			
Max. Battery discharge efficiency (BAT to AC)(@full load) [%]	97.50			
SAFETY & PROTECTION				
Over/under voltage protection	Yes			
DC isolation protection	Yes			
Grid protection	Yes			
DC injection monitoring	Yes			
Residual current detection	Yes			
Anti-islanding protection	Yes			
Over load protection	Yes			
Over heat protection	Yes			
General Data				
Dimension [W/H/D](mm)	430*341.5*143			
Dimension of packing [W/H/D](mm)	554*446*259			
Net weight [kg]	15.5	15.5	16.3	16.3
Gross weight [kg]	18.5	18.5	19.3	19.3
Installation	Wall-mounted			
Operating temperature range[°C]	-20~+60 (derating at 45)			
Storage temperature [°C]	-20~+60			
Storage/Operation relative humidity	0~100%, condensing			
Altitude [m]	≤2000			
Ingress Protection	IP65(for outdoor use)			
Protective Class	I			
Over Voltage Category	III(MAINS), I(DC)			
Pollution Degree	III			
Cooling	Natural			
Inverter Topology	Non-isolated			
Communication interface	RS485, Meter(optional), Wifi(optional), RF(optional), DRM, CAN, USB			
Certification	G83,G59			